## TECHNICAL DATASHEET



**TERRAPLAST PLUS S20P** 



			EIN 15252
Product:	TERRAPLAST PLUS S20P - perforated dimpled sheet		1
Supplier:	MASTERPLAST International Kft., 8143 Sárszentmihály, Árpád u. 1/a (www.masterplastgroup.com)		1000000000000000
Size, packaging:	2,0 m wide / 20m long roll		
Application:	Water-retaining and drainage layer in soil-covered flat garden roofs, in addition the mechanical protection of the water-proofing in green roof structures. The sheets (laid with dimples downwards and perforated sheet upwards) prevent the fast dehydration of the vegetation, while excess water is drained away through the perforation and the waterproofing.		
Material:	High-density polyethylene (HD-PE)		
Properties		Relevant standards	Technical data
Width		EN 1848 - 2	2,0 m (±2 %)
Length		EN 1848 - 2	20 m (±2 %)
Mass per unit area		EN 1849 - 2	1000 g/m <sup>2</sup> (±5 %)
Hight of knobs		MDV	20 mm (±10 %)
Durability against ageing		EN 1296, EN 1928	pass
Durability against chemicals		EN 1847, EN 1928	pass
Mecha	nical properties		
Compression strength (at ~15% compression) after short time load		EN ISO 25619-2	150 (±30) kN/m² (=kPa)
Tensile strength (MD/CMD)		EN ISO 10319	9 (-2) kN/m / 9 (-2) kN/m
Elongation (MD/CMD)		EN ISO 10319	35 (±15) % / 35 (±15) %
Drai	nage capacity		
Water storage capacity		MDV	5,8 l/m²
Waterflow estimated value (Horizontal application; 20kPa, i=0,04)		EN ISO 12958	2,5 l/(m.s) (-20)%
Waterflow estimated value (Horizontal application; 20kPa, $i{=}0{,}1)$		EN ISO 12958	4,3 l/(m.s) (-20)%
Storage and handling	Under dry conditions, pr	otected against sun-radiation and other hea	t cources

Under dry conditions, protected against sun-radiation and other heat sources.

Guarantee, warranty

In accordance with the current legislations and the conditions of the distributor. The observation of the application rules of the product and presentation of the invoice constitute a prerequisite for possible future warranty claims. The product must be covered within 14 days after installation. Min 5 years warranty against rotting under normal circumstances occuring in natural soils (with 4<pH<9 and soil temperature <25°C).

Standards, specifications

EN 13252

Health and safety

No labelling required in accordance with the relevant regulation (EC) No. 1907/2006 of the European Parliament and of the Council (REACH).

This datasheet corresponds to our current knowledge, experiences and general informations on the subject, but may be revised as new knowledge and/or experience becomes available. It does not imply any legally binding assurance. The product possesses the given technical characteristics. Since all variations of end-using of the product can not be anticipated, the designer/end-user's responsibility to make sure of the suitability of this product for particular purposes, structures.

This technical datasheet is applied to products sold by Masterplast International Kft. and valid until withdrawal or until modification. Since this datasheet may be subject to revision, it is the responsibility of designer/end-user to make sure of possessing the latest version of the datasheet (\*see date of issuing). Most recent version of this datasheet can be also accessed under www.masterplastgroup.com. Modification of the technical datasheet repeals the previously issued versions!

TD\_TERRAPLAST.PLUS.S20P.T-20181121\_EN

\*Issued: 2018. 11. 21.